

RECIPROCATING COMPRESSOR CIRCULATION OIL (ISO VG 220)  
STRAIGHT MINERAL OIL WITH R&O ADDITIVES  
ACCORDING TO DIN 51524 PART 1(HL)  
& DIN 51517 PART 2 (CL) & ISIRI-6423  
VISCOSITY IN 40 C: 198-242 CST (ASTM D-445)  
VISCOSITY INDEX: >100 (ASTM D-2270)  
POUR POINT:< -12 C (ASTM D-97)  
FLASH POINT: >240 C (ASTM D-92)  
TAN : < 0.15 MG KOH/G (ASTM D-664)  
FOAM TEST (SEQ. I , II, III, ): 75,25,75 (ASTM D-892)  
RUST RESISTANCE :PASS (ASTM D-665 A)  
COPPER CORROSION : < 2 DEGREE (ASTM D-130)  
WATER SEPARABILITY AT 82 C : < 30 MIN.(ASTM D-1401),  
OXIDATION STABILITY AFTER 1000 HR : < 2 MG KOH/G (ASTM-D94)  
ALL CHARACTERISTICS SHOULD BE PASSED AND VERIFICATED BY  
APPROVED LABORATORY, NOTE: MATERIAL SAFETY DATA SHEETS  
(MSDS) IS ESSENTIAL FOR TECHNICAL EVALUATION  
MANUFACTURE & TRADE MARK, ORDER NO., MESC NO.  
PRODUCT DATE, EXPIRY DATE & MSDS TO BE MARKED  
ON BODY OF DRUMS  
PALLETIZED ON REINFORCED PVC PALLETS  
METAL STRAPPED(2 NUMBERS HORIZONTALLY & 2 NUMBERS VERTICAL  
REF. BP ENERGOL CS 220 OR APPROVED EQUIVALENT  
DR 80 RECIPROCATING COMPRESSOR CIRCULATION OIL, IN 208 LITRE DRU  
030205 L N

✓ VG220 روغن جریس

OF INDENT NO.: SJS 0333026

ITEM COUNT: 1

L: LAND T: TRAIN O: OVERLAND